### KT-KD61

#### vMix Slow Motion Instant Replay

Instant Replay for 8 Channels

T-type speed control handle

Bidirectional communicate with mainstream software

2-level variable-speed jog shuttle

Broadcast-grade multi-channel A/B source switching

Multiple control Interfaces reserved





### **Features**

#### Slow motion replay:

Support quickly set in-points (IN) and out-points (OUT) for the connected camera positions. The in-point marks the start, and playback begins at the out-point.

#### 2-Level searchable jog shuttle design:

2-level adjustable variable-speed video content search jog shuttle design, integrated with in and out point buttons for accurate frame marking and extraction.

#### High quality aluminum alloy T-BAR fader:

Aluminum alloy high-quality T-BAR fader, combined with LED light progress bar, employs a multi-point calibration algorithm for precise field-based adjustments and control.

#### Precision-machined aluminum alloy enclosure:

USB integrated communication and power supply, aluminum alloy CNC process shell.

#### 42 Dual-Color Transparent Crystal Buttons:

42 High-Quality Dual-Color Crystal Clear Buttons, based on communication protocols such as MIDI, USB, RS232 (reserved), LAN (reserved);

#### ■ Broadcast-grade multi-channel A/B source switching:

Broadcast-grade multi-channel A/B camera switching, 8 shortcut keys for multiple operations on the current channel event;

#### Mark-in preset button:

Equipped with 3 quick -5, -10, -20 second preset buttons for quick marking, to swiftly complete current event interception and marking.

### **Specifications**

Main Function		
Signal Source	8-channel A and B camera	
Backlit function	Red and green-two colorful crystal buttons	
keys		
T-BAR fader	T-type speed control handle	
Jog Shuttle	2-Level Variable-Speed Jog Shuttle	
Supported	vMix, SINSAM and other MIDI communication compatible software	
Software	can be used	
Control		
Control Interface	USB, RJ45 (Reserved), RS232 (Reserved)	
Power Supply		
Input Voltage	USB 5V	
Input Current	0.15A	
Rated Power	1W	

KATO VISION CO., LTD
Web: www.katovid.com Email: info@katovision.com



Powered by USB	Support(rely on the USB power supply capability of the computer)	
Others		
Environment	Indoors	
Operating	-25℃~60℃	
temperature		
Humidity	Less 90%	
environment		
Dimensions	325*246*98mm	
Net Weight	3.5KG	
Material	Aluminum Alloy	
Color	Black	

# **Application Scenario**















# **Dimension**
















## Connection

